# PRESIDENT TITANIUM CO., INC.



# SAFETY DATA SHEET

243 FRANKLIN ST. - HANSON, MA 02341 WWW.PRESIDENTTITANIUM.COM

ISSUE DATE: 01-JAN-16 REVISION DATE: 01-FEB-23 VERSION: 03

## IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier / Product Name: Titanium & Titanium Alloys

Other means of identification: 6AL/4V Grade 5 / 6AL/4V Grade 23 (ELI) / CP-Grade 4 / CP-Grade 2

**Recommended Use:** Titanium & Titanium Alloy product manufacture (i.e. forging, casting, welding,

cutting, etc. for aerospace, medical, military, and/or commercial applications).

Recommended Restrictions: None

Distributor Information: President Titanium Co., Inc. – 243 Franklin Street – Hanson, MA 02341 U.S.A.

Phn: (781) 294-0000 / Fax: (781) 293-3753 / Web: www.presidenttitanium.com

**Emergency Information:** CHEMTREC: 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

## Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

## **Label Elements**

**Emergency Overview** 

Appearance	Physical State	Odor
various product forms	solid	odorless

# Hazards not otherwise classified (HNOC)

Not applicable

## Other Information

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, and/or other similar heat-generating processes, airborne particles and/or fumes may cause general irritation of the eyes, nasal, and lungs. There is also the chance of the following potentially hazardous airborne particles and/or fumes that may be generated:

- titanium dioxide an IARC Group 2B carcinogen
- vanadium pentoxide (V2O5) affects eyes, skin, respiratory system

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

# Synonyms (partial list):

6AL/4V Grade 5 Titanium, 6AL/4V ELI (Grade 23) Titanium, CP-Grade 4 Titanium, CP-Grade 2 Titanium

Chemical Name	CAS No.	Weight-%
Titanium (TI)	7440-32-6	88 - 100
Aluminum (AL)	7429-90-5	0 - 6.75

Vanadium (V)	7440-62-2	0 - 4.5
Iron (FE)	7439-89-6	< 0.5
Oxygen (O)	7782-44-7	< 0.4
Carbon (C)	7440-44-0	< 0.08
Nitrogen (N)	7727-37-9	< 0.05
Hydrogen (H)	1333-74-0	< 0.015
Yttrium (Y)	7440-65-5	< 0.005
Other	N/A	< 0.1

highlighted indicates < 1/2 % weight

## 4. FIRST AID MEASURES

#### First aid measures

110000100	
Eye contact	In the case of particles coming in contact with eyes during processing, treat as with any foreign object.
Skin Contact	In the case of skin irritation or allergic reactions see a physician.
Inhalation	If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove to fresh air and consult a qualified health professional.
Ingestion	Not an expected route of exposure.

## Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergic skin reaction.

## Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
--------------------	------------------------

# 5. FIRE-FIGHTING MEASURES

# Suitable extinguishing media

Not flammable in the form of this product as distributed, flammable as finely divided particles or pieces resulting from processing of this product. Smother with salt (NaCl) or class D dry powder fire extinguisher.

## Unsuitable extinguishing media

Do not spray water on burning metal as an explosion may occur. This explosive characteristic is caused by the hydrogen and steam generated by the reaction of water with the burning material.

# Specific hazards arising from the chemical

Intense heat. Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

# **Hazardous combustion products**

Titanium dioxide an IARC Group 2B carcinogen, Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Vanadium pentoxide (V2O5) affects eyes, skin, respiratory system, zinc, copper, magnesium, or cadmium fumes may cause metal fume fever. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

## **Explosion data**

Sensitivity to Mechanical Impact	None
Sensitivity to Static Discharge	None

# Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved (or equivalent) respirator and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

**Personal precautions**Use personal protective equipment as required.
For emergency responders
Use personal protective equipment as required.

**Environmental precautions** 

**Environmental precautions** Not applicable to massive product.

# Methods and material for containment and cleaning up

Methods for containmentNot applicable to massive product.Methods for cleaning upNot applicable to massive product.

## 7. HANDLING AND STORAGE

## Precautions for safe handling

Advice on safe handling Very fine, high surface area material resulting from grinding, buffing, polishing, or similar

processes of this product may ignite spontaneously at room temperature.

WARNING: Fine particles resulting from grinding, buffing, polishing, or similar processes of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to

minimize combustible dust hazard.

# Conditions for safe storage, including any incompatibilities

Storage Conditions Keep chips, turnings, dust, and other small particles away from heat, sparks, flame and

other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Dissolves in hydrofluoric acid / Ignites in the presence of fluorine.

When heated above 200°C, reacts exothermically with the following. Chlorine, bromine,

halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Control parameters**

## **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL
Titanium		
7440-32-6		
Aluminum	TMA: 1 mg/m³ recaireble fraction	TWA: 15 mg/m <sup>3</sup> total dust
7429-90-5	TWA: 1 mg/m³ respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable fraction
Vanadium		Ceiling: 0.5 mg/m <sup>3</sup> V2O5 respirable dust
7440-62-2		Ceiling: 0.1 mg/m <sup>3</sup> V2O5 fume
Iron		
7439-89-6		

## Appropriate engineering controls

**Engineering Controls** Avoid generation of uncontrolled particles.

## Individual protection measures, such as personal protective equipment

**Eye/face protection** When airborne particles may be present, appropriate eye protection is recommended.

For example, tight-fitting goggles, foam-lined safety glasses or other protective

equipment that shield the eyes from particles.

**Skin and body protection** Fire/flame resistant/retardant clothing may be appropriate during hot work with the

product. Wear protective gloves. Cut-resistant gloves and/or protective clothing may be

appropriate when sharp surfaces are present.

**Respiratory protection** When particulates/fumes/gases are generated and if exposure limits are exceeded or

irritation is experienced, proper approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminant

concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** 

Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Solid

AppearanceVarious massive product formsOdorOdorlessColormetallic, gray or silverOdor thresholdNot applicable

<u>Property</u> <u>Values</u> <u>Remarks \* Method</u>

Ph Not applicable

Melting point/freezing point 1540-1670 °C 2800-3000 °F

Boiling point / boiling range-----Not applicableFlash point-----Not applicableEvaporation rate-----Not applicable

Flammability (solid, gas) ----- Not flammable in the form of this product as

distributed, flammable as finely divided particles or pieces resulting from processing of product

Flammability Limit in Air

**Upper flammability limit:** Not applicable **Lower flammability limit:** Not applicable

Vapor pressure-----Not applicableVapor density-----Not applicable

Specific Gravity 4.5

Water solubility Insoluble Insoluble Solubility in other solvents Not applicable Partition coefficient Not applicable Autoignition temperature Not applicable **Decomposition temperature** Not applicable Kinematic viscosity Not applicable ----**Dvnamic viscosity** Not applicable

**Explosive properties**Not applicable **Oxidizing properties**Not applicable

Other Information

Softening point
Molecular weight
VOC Content (%)
Not applicable
Not applicable

Density ----Bulk density -----

# 10. STABILITY AND REACTIVITY

# Reactivity

Not applicable

## Chemical stability

Stable under normal conditions.

## **Possibility of Hazardous Reactions**

None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

### Conditions to avoid

Dust formation and dust accumulation.

#### Incompatible materials

Dissolves in hydrofluoric acid, ignites in the presence of fluorine.

When heated above 200°C, reacts exothermically with the following: chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

# **Hazardous Decomposition Products**

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heatgenerating processes, the following potentially hazardous airborne particles and/or fumes may be generated:

- titanium dioxide an IARC Group 2B carcinogen
- Vanadium pentoxide (V2O5) affects eyes, skin, respiratory system

# 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

## **Product Information**

• Inhalation Not an expected route of exposure for product in massive form.

Eye contact
 Not an expected route of exposure for product in massive form.

Skin Contact May cause sensitization by skin contact.

Ingestion
 Not an expected route of exposure for product in massive form.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium 7440-32-6	> 5000 mg/kg bw		
Aluminum 7429-90-5	15,900 mg/kg bw		> 1 mg/L
Vanadium 7440-62-2	> 2000 mg/kg bw		
Iron 7439-89-6	98,600 mg/kg bw		> 0.25 mg/L

## Information on toxicological effects

**Symptoms** May cause sensitization by skin contact.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Product not classified.

Skin corrosion/irritation Product not classified.

Serious eye damage/eye irritation Product not classified.

**Sensitization** May cause sensitization by skin contact.

**Germ cell mutagenicity** Product not classified. **Carcinogenicity** Product not classified.

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

This product contains a chemical which is listed as a severe marine pollutant according to DOT

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Titanium 7440-32-6	The 72 h EC50 of titanium dioxide to Pseudokirchnerella subcapitata was 61 mg of TiO2/L	The 96 h LC50 of titanium dioxide to Cyprinodon variegatus was greater than 10,000 mg of TiO2/L. The 96 h LC50 of titanium dioxide to Pimephales promelas was greater than 1,000 mg of TiO2/L	The 3 h EC50 of titanium dioxide for activated sludge were greater than 1000 mg/L	The 48 h EC50 of titanium dioxide to Daphnia Magna was greater than 1000 mg of TiO2/L
Aluminum 7429-90-5	The 96-h EC50 values for reduction of biomass of Pseudokirchneriella	The 96 h LC50 of aluminum to Oncorhynchus mykiss		The 48-hr LC50 for Ceriodaphnia dubia exposed to Aluminium

	subcapitata in AAP- Medium at pH 6, 7, and 8 were estimated as 20.1, 5.4, and 150.6 µg/L, respectively, for dissolved Al	was 7.4 mg of Al/L at pH 6.5 and 14.6 mg of Al/L at pH 7.5		chloride increased from 0.72 to greater than 99.6 mg/L with water hardness increasing from 25 to 200 mg/L
Vanadium 7440-62-2	The 72 h EC50 of vanadium pentoxide to Desmodesmus subspicatus was 2,907 ug of V/L	The 96 h LC50 of vanadium pentoxide to Pimephales promelas was 1,850 ug of V/L	The 3 h EC50 of sodium metavanadate for activated sludge was greater than 100 mg/L	The 48 h EC50 of sodium vanadate to Daphnia magna was 2,661 ug of V/L
Iron 7439-89-6		The 96 h LC50 of 50% iron oxide black in water to Danio rerio was greater than 10,000 mg/L	The 3 h EC50 of iron oxide for activated sludge was greater than 10,000 mg/L	The 48 h EC50 of iron oxide to Daphnia magna was greater than 100 mg/L

# Persistence and degradability

.

**Bioaccumulation** 

.

Other adverse effects

### 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging None anticipated.

**Disposal:** Scrap should be recycled whenever possible. Product dusts and fumes from processing operations should also be recycled or classified by a competent environmental professional and disposed of in accordance with applicable federal, state or local regulations.

**Container Cleaning and Disposal:** This product as supplied does not possess characteristics which qualify as hazardous waste. Following processing and use, resulting titanium powders, fines and/or swarf will impact cleaning and disposal and should be evaluated by a competent environmental professional.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

## 15. REGULATORY INFORMATION

## **International Inventories**

**TSCA** Complies DSL/NDSL Complies **EINECS/ELINCS** Complies Complies **ENCS IECSC** Complies **KECL** Complies Complies **PICCS AICS** Complies

#### <u>Legend:</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS - Japan Existing and New Chemical Substances** 

**IECSC -** China Inventory of Existing Chemical Substances

**KECL - Korean Existing and Evaluated Chemical Substances** 

**PICCS - Philippines Inventory of Chemicals and Chemical Substances** 

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains no chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

# **SARA 311/312 Hazard Categories**

•	Acute health hazard	No
•	Chronic health hazard	No
•	Fire hazard	No
•	Sudden release of pressure hazard	No
•	Reactive hazard	No

## **CWA (Clean Water Act)**

This product does not contain any substances which are listed as regulated pollutants, pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

## **CERCLA**

This material, as supplied, contains none of the substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

# **US State Regulations**

California Proposition 65 - This product contains none of the Proposition 65 chemicals

# **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Titanium 7440-32-6	X		
Aluminum 7429-90-5	X	X	X
Vanadium 7440-62-2	Х	Х	Х

# **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

## **16. OTHER INFORMATION**

<u>NFPA</u>	<b>Health hazards</b> - 0	Flammability - 0	Instability - 0	Physical and Chemical
				Properties - n/a
<u>HMIS</u>	Health hazards - 1*	Flammability - 0	Physical Hazards – 0	Personal Protection – X
	Chronic Hazard Star Legend * = Chronic Health Hazard			

<u>Note:</u> The information provided in this safety data sheet is correct to the best of our knowledge and belief at the original date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and/or release and is NOT to be considered in any way a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# **REVISION HISTORY**

REV. 00 (01-JAN-16) INITIAL RELEASE	
REV. 01 (30-APR-18) REVIEWED AND AFFIRMED - MINOR EDITORIAL CHANGES	
REV. 02 (30-APR-20) REVIEWED AND AFFIRMED - NO CHANGES	
REV. 03 (01-FEB-23) REVIEWED AND AFFIRMED - NO CHANGES	